

## 3/2- and 5/2-way spool valves with NAMUR style interface and combined spring return

Обновлено: 05.01.24

### Характеристики

<b>Рабочие среды</b>	Air, neutral gases, filtered
<b>Соединение 1</b>	G 1/4"
<b>Рабочее давление</b>	1.5 to 10 bar (552.11 and 552.12); 2.5 to 10 bar (552.21 and 552.22)
<b>Рабочая температура</b>	-20 °C to +50 °C
<b>Подключение к электросети</b>	Plug connector PG 9
<b>Потребляемая мощность</b>	3 W=/5 VA~
<b>Корпус</b>	Anodised aluminium
<b>Заслонка</b>	Stainless steel
<b>Уплотнение</b>	Нитрильный каучук
<b>Соединение 3 + 5</b>	G 1/4"



### Информация о продукте

<b>Напряжение</b>	230 V, 50 Hz
<b>Port 1</b>	G 1/4"

<b>DN</b>	7
<b>Расход ном.</b>	1250 l/min

DN = номинальный диаметр, номинальный внутренний диаметр

### Указания

Прочие данные только по запросу.

### Описание

Pilot-operated 3/2- and 5/2-way spool valves with threaded ports and a NAMUR style interface with air purging function. By adding the conversion plate supplied with each valve, the device can be adapted to 3/2-way function. Filter regulators are also available with bowl guard or metal bowl. Filter regulators are also available in lockable version. Please ask for more information.

### Комплект поставки

Plug connector PG 9, conversion plate, screws and seal