

3/2- and 5/2-way spool valves with NAMUR style interface and combined spring return

Обновлено: 05.01.24

Характеристики

Рабочие среды	Air, neutral gases, filtered
Соединение 1	G 1/4"
Рабочее давление	1.5 to 10 bar (552.11 and 552.12); 2.5 to 10 bar (552.21 and 552.22)
Рабочая температура	-20 °C to +50 °C
Подключение к электросети	Plug connector PG 9
Потребляемая мощность	3 W=/5 VA~
Корпус	Anodised aluminium
Заслонка	Stainless steel
Уплотнение	Нитрильный каучук
Соединение 3 + 5	G 1/4"



Информация о продукте

Напряжение	24 V DC
Port 1	G 1/4"

DN	7
Расход ном.	1250 l/min

DN = номинальный диаметр, номинальный внутренний диаметр

Указания

Прочие данные только по запросу.

Описание

Pilot-operated 3/2- and 5/2-way spool valves with threaded ports and a NAMUR style interface with air purging function. By adding the conversion plate supplied with each valve, the device can be adapted to 3/2-way function. Filter regulators are also available with bowl guard or metal bowl. Filter regulators are also available in lockable version. Please ask for more information.

Комплект поставки

Plug connector PG 9, conversion plate, screws and seal