

### Характеристики

<b>Рабочие среды</b>	Filtered, unlubricated compressed air
<b>Диапазон давлений</b>	0 - 7 bar (NC) with silver plate at manual override 0 - 5 bar (NO) with black plate at manual override
<b>Соединение</b>	In manifold base
<b>Область температур</b>	-5 °C to +45 °C
<b>Мощность катушки</b>	2.5 W
<b>Материал</b>	Пластмасса
<b>Уплотнение</b>	NBR, stainless steel
<b>Дополнительная информация</b>	Wichtiger Hinweis: Stecker im Lieferumfang nicht enthalten. Bitte separat mitbestellen. Öffnungszeit/Schließzeit 10 - 12 ms (druckabhängig)



### Информация о продукте

<b>Функция</b>	NC
<b>Напряжение</b>	12 V DC
<b>Соединение</b>	Cable (30 cm)

<b>Соединение</b>	Cable (30 cm)
<b>H</b>	42 mm
<b>B</b>	15 mm

### Указания

Прочие данные только по запросу.

### Описание

Directly controlled 3/2-way solenoid valves specially designed for pneumatic applications. These valves are provided with a flange for assembly on an individual base or multiple manifold base. They feature a monostable manual operator. The scope of supply includes two fixing bolts and a flange gasket. The coils can be turned 180°.

### Дополнительная информация

Important: The scope of supply does not include a connector. Please order separately. Opening time/closing time 10 - 12 ms (depending on pressure)