

Round cylinders, single-acting (pressureless in the retracted position), with magnet, non-cushioned, »MSI«

Series

Характеристики

| | |
|---------------------------|--|
| Рабочие среды | Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous. |
| Рабочее давление | 1 - 10 bar (double-acting); 2 - 10 bar (single-acting) |
| Область температур | -20 °C to +70 °C |
| Поршневой шток | Stainless steel 1.4301 |
| Исполнение | Type "CA" = ground cover with threaded pin - swivel design Type "CM" = ground cover with threaded pin round - swivel design |
| Поршни | Stainless steel 1.4305 (8 to 12 mm); Alu (16 to 40 mm) |
| Труба цилиндра | Stainless steel 1.4301 |
| Уплотнение | Нитрильный каучук |



Информация о продукте

| | | | |
|---------------------------|-------|--|-----------|
| Ø поршня | 8 mm | Ø поршневого штока | 4 mm |
| Ход | 30 mm | Исполнение | »CA« type |
| Ø поршневого штока | 4 mm | Внешняя резьба поршневого штока | M 4 x 0,7 |

Указания

Прочие данные только по запросу.

Описание

Series "MSI" single-acting, pressureless retraction, Ø 8 - 40