

Характеристики

Рабочие среды	Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.
Рабочее давление	Max. vacuum 10 bar (external pilots), 3 to 7 bar (internal pilots as standard)
Управляющее давление	3 - 7 bar
Область температур	-10 °C to +60 °C
Расход	200 NI/min (Ø 4), 500 NI/min (Ø 6), 800 NI/min (Ø 8)
Функция	Blind (terminates the system)
Потребляемая мощность	0.6 W per pilot
Степень защиты	IP 65
Дополнительная информация	Wichtiger Hinweis: Stecker im Lieferumfang nicht enthalten. Bitte separat mitbestellen. Anzahl der Ansteuerungen bis 16 Betätigungen (z. B. 16 federrückgestellte Ventile). Handhilfsbetätigung rastend (bistabil), auf Anfrage in monostabiler Ausführung (tastend) lieferbar



Информация о продукте

Функция	Blind (terminates the system)
----------------	-------------------------------

Функция	Blind (terminates the system)
----------------	-------------------------------

Указания

Прочие данные только по запросу.

Описание

These compact valve terminals, with a maximum flow rate of 800 NI/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates. Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.

Дополнительная информация

Important: The scope of supply does not include a connector. Please order separately. Max. 16 (e.g. 16 spring return valves) working pressure. Manual control Latching (bistable), Monostable (non-latching) version also available on request