

## Pressure gauge stopcocks, female - loose (rotatable) female

Обновлено: 05.03.24

### Характеристики

|                                  |   |
|----------------------------------|---|
| <b>Применение</b>                | For all pressure gauges with a flat gasket acc. to DIN 16258  |
| <b>Диапазон давлений</b>         | Max. 16 bar, depending on the variant. Pressure gauge valves should be used for higher pressures                            |
| <b>Температура</b>               | max. 50 °C  |
| <b>Ручка</b>                     | Plastic   |
| <b>Корпус</b>                    | Brass with a bare metal surface or stainless steel 1.4571   |
| <b>Дополнительная информация</b> | Weitere Messbereiche auf Anfrage<br>Ausführung für Fronttafeleinbau auf Anfrage<br>Ausführung mit Schleppzeiger auf Anfrage |
| <b>Контрольный фланец</b>        | -   |



### Информация о продукте

|                 |        |                 |        |
|-----------------|--------|-----------------|--------|
| <b>Материал</b> | Латунь | <b>Резьба</b>   | G 1/2  |
| <b>SW</b>       | 27 mm  | <b>PN (бар)</b> | 25     |
| <b>Резьба</b>   | G 1/2  | <b>Материал</b> | Латунь |

### Указания

Прочие данные только по запросу. K-07201090, K-07201091 in acc. with DIN 16261-A, K-07201096, K-07201097 in acc. with DIN 16261-B K-07201128, K-07201129 in acc. with DIN 16262-A, K-07201127 in acc. with DIN 16262-B

### Описание

It is useful to install a stopcock as a shut-off element between the pressure gauge and the pipe. When the lever is set to the »blow out« position, the medium is discharged into the atmosphere. Stopcocks with a test port allow pressure gauges to be simultaneously connected to the pipe.

### Дополнительная информация

Further measuring ranges on request Version for panel mounting available on request. Version with max. pointer available on request