

Pressure transmitters for universal industrial applications, nonlinearity 0.25%

Обновлено: 04.26.24

Характеристики

Тип	S-20
Напряжение	DC 8 ... 36 V
Подключение к электросети	With right-angle connector acc. to DIN EN 175301-803 A
Степень защиты	IP 65 acc. to EN 60529
Выходной сигнал	4 to 20 mA, 2-wire
Нелинейность	up to 0.25% of span
Температура среды	-30 °C to +100 °C
Температура окружающей среды	-40 °C to +70 °C
Корпус	CrNi steel 1.4571
Детали, контактирующие с измеряемой средой	CrNi steel 1.4571
Дополнительная информация	Weitere Messbereiche auf Anfrage Optional auf Anfrage stehen für hohe Medientemperaturen (bis zu +150 °C) auch Druckmessumformer mit Kühlstrecke zur Verfügung.



Информация о продукте

Диапазон измерений	-1 / 0.0 bar	Резьба	G 1/2
---------------------------	--------------	---------------	-------

Описание

Pressure transmitters, very high precision, in CrNi steel, for complex measurement tasks in the process industry as well as research and development. Applications: Low temperature or outdoor applications, extreme shock loads and vibration levels, corrosive media in the chemical industry. Compatible with all internationally established process connections.

Дополнительная информация

Further measuring ranges on request There are also pressure converters with cooling fins available optionally on request for high media temperatures (up to +150 °C).