

### Характеристики

<b>Кольцо круглого сечения</b>	Нитрильный каучук
<b>Область температур</b>	-20 °C to +80 °C (G 1/4 to G 1/2) -20 °C to +120 °C (G 3/4 to G 2)
<b>макс. входное давление</b>	18 bar (G 1/4 to G 3/4); 35 bar (G 1 to G 2)
<b>Корпус</b>	Aluminium
<b>Поршни</b>	Polyacetate (G 1/4 to G 1/2); Aluminium (G 3/4 to G 2)
<b>Дополнительная информация</b>	Einbau vor einer Kupplung (Übergangsstelle feste Verrohrung zu Verteilerdose/Kupplung), nach einer Wartungseinheit



### Информация о продукте

<b>SW</b>	22 mm	<b>Длина</b>	57 mm
<b>Длина</b>	57 mm	<b>Резьба</b>	G 1/4" male / female

### Указания

Прочие данные только по запросу.

### Описание

Efficient protection for ruptured hoses or pipes in pneumatic systems. Preset to permit normal air consumption by pneumatic tools. Hose Guard detects a rupture in a hose or pipe and interrupts the supply of compressed air in a fraction of a second apart from a minimal residual flow. Unaffected parts of the compressed air system remain fully pressurised, so that the damaged hose or segment can be replaced without difficulty. Once the ruptured hose or pipe has been repaired, the replaced segment gradually fills to its working pressure level. As soon as this occurs, Hose Guard opens the line again for normal operation. Hose Guard protects personnel, machinery and plant against damage if a pneumatic system or hose ruptures, complies with the EU standard DIN EN ISO 4414: 2010, 2011-04 - § 5.4.5.11, is reliable and tamper-proof, can be installed in any pneumatic system, bears the TÜV test mark 01-02-0145.

### Указание по заказу

ATTENTION: For suitable hoses, please check the respective data sheet.

### Дополнительная информация

Installation upstream of a coupling (connector between hard piping and junction box/coupling) and downstream of a service unit