

Характеристики

Свойства	Support surfaces on the bottom higher suction power at narrow workpieces
Область применения	Handling of narrow parts and bars Handling of parts which only have narrow and small places to grab them.
Дополнительная информация	Achtung: Anschlussnippel nicht im Preis enthalten, bitte separat bestellen.



Информация о продукте

Габаритная высота с ниппелем (внутренняя резьба)	22	Габаритная высота с ниппелем (наружная резьба)	17
Соединительный ниппель с внешней резьбой	K-07450010	Ø1 x Ø2 овал	15.0 mm x 5.0 mm
Габаритная высота с ниппелем (наружная резьба)	17	Соединительный ниппель с внутренней резьбой	K-07450012

Указания

Прочие данные только по запросу. Mini-sensor with housing and connection cable, analogue or digital output signal. Minimum size and low weight combined with high measuring accuracy.

Описание

Robust and hard-wearing suction pad with a single, oval-shaped sealing lip. Used wherever objects (parts, packing materials, etc.) need to be lifted, transported, turned over or handled in some other manner. It is also ideal when it is necessary to handle long or flat workpieces. Due to its oval shape, it has a considerably higher suction force than round, flat suction pads when handling narrow or long workpieces. It acts as the connecting element between the vacuum generator and the workpiece.

Дополнительная информация

Important: The price does not include connection nipples. Please order separately.