

Характеристики

Область применения Крепления шлангов в области низких давлений

Материал нержавеющая сталь



Артикул

Наименование	Диапазон зажима (мм)	Ширина ленты
1OK2.9-3.3-3VA	2,7 - 3,3	3,0
1OK3.0-3.5-3VA	3,0 - 3,5	3,0
1OK3.3-4.1-4VA	3,3 - 4,1	4,0
1OK4.1-5.1-4VA	4,1 - 5,1	4,0
1OK5.1-6.1-4VA	5,1 - 6,1	4,0
1OK5.6-6.6-4VA	5,6 - 6,6	4,0
1OK6.1-7.0-4VA	6,1 - 7,0	5,0
1OK6.5-7.5-5VA	6,5 - 7,5	5,0
1OK6.8-8.0-5VA	6,8 - 8,3	5,0
1OK7.1-8.3-5VA	7,1 - 8,3	5,0
1OK7.5-8.7-5VA	7,5 - 8,7	5,0
1OK7.5-9.0-6VA	7,5 - 9,0	6,0
1OK8.1-9.5-6VA	8,1 - 9,5	6,0
1OK8.5-10.0-6VA	8,5 - 10,0	6,0
1OK9.1-10.5-6VA	9,1 - 10,5	6,0
1OK9.3-11.0-6VA	9,3 - 11,0	6,0
1OK9.6-11.3-6VA	9,6 - 11,3	6,0
1OK09-11VA	9,0 - 11,0	6,5
1OK10.1-11.8-6VA	10,1 - 11,8	6,0
1OK10.1-12.0-6VA	10,1 - 12,0	6,0
1OK10.3-12.3-6VA	10,0 - 12,3	6,0
1OK10.8-12.8-6VA	10,8 - 12,8	6,0
1OK11-13VA	11,0 - 13,0	6,5
1OK11.3-13.3-6VA	11,3 - 13,3	6,0
1OK11.8-13.8-6VA	11,8 - 13,8	6,0
1OK12-14VA	12,0 - 14,0	7,0
1OK12.0-14.0-6VA	12,0 - 14,0	6,0
1OK12.5-14.5-6VA	12,5 - 14,5	6,0
1OK13.0-15.0-6VA	13,0 - 15,0	6,0
1OK13.5-15.5-6VA	13,5 - 15,5	6,0
1OK13.8-16.0-6VA	13,8 - 16,0	6,0
1OK14-16VA	14,0 - 16,0	7,0
1OK14.0-16.5-6VA	14,0 - 16,5	6,0
1OK14.6-16.8-6VA	14,6 - 16,8	6,0
1OK15.3-17.5-6VA	15,3 - 17,5	6,0
1OK16-18VA	16,0 - 18,0	7,0
1OK16.3-18.5-6VA	16,3 - 18,5	6,0
1OK17-19VA	17,0 - 19,0	7,0
1OK17.2-19.5-6VA	17,2 - 19,5	6,0
1OK17.7-20.0-7VA	17,7 - 20,0	6,0
1OK17.9-20.7-7VA	17,9 - 20,7	6,0
1OK18-20VA	18,0 - 20,0	6,0
1OK18.7-21.0-7VA	18,7 - 21,0	6,0
1OK19.5-21.8-7VA	19,5 - 21,8	6,0
1OK19.9-22.5-7VA	19,9 - 22,5	7,0
1OK21.0-23.5-7VA	21,0 - 23,5	6,0
1OK21.7-24.5-7VA	21,7 - 24,5	6,0
1OK22.7-25.5-7VA	22,7 - 25,5	6,0
1OK23.6-26.3-7VA	23,6 - 26,3	6,0
1OK24.1-27.0-7VA	24,1 - 27,0	6,0
1OK27.2-30.7-7VA	27,2 - 30,7	6,0