

Характеристики

Область применения	Крепления шлангов в области низких давлений
Материал	нержавеющая сталь



Артикул

Наименование	Диапазон зажима (мм)	Ширина ленты
2OK3-5VA	3,4 - 5,0	5,0
2OK3.1-4.1VA	3,1 - 4,1	3,5
2OK3.5-4.5VA	3,5 - 4,5	3,5
2OK5-7VA	5,0 - 7,0	6,0
2OK7-9VA	7,0 - 9,0	6,0
2OK8-11VA	8,0 - 11,0	7,0
2OK9-11VA	9,0 - 11,0	6,5
2OK11-13VA	11,0 - 13,0	6,5
2OK13-15VA	13,0 - 15,0	7,0
2OK15-17VA	15,0 - 17,0	7,5
2OK15-18VA	15,0 - 18,0	7,5
2OK17-20VA	17,0 - 20,0	7,5
2OK18-21VA	18,0 - 21,0	8,0
2OK19-22VA	18,1 - 22,0	9,0
2OK20-23VA	20,0 - 23,0	8,0
2OK22-25VA	22,0 - 25,0	8,5
2OK23-27VA	23,0 - 27,0	8,5
2OK25-28VA	25,0 - 28,0	9,0
2OK27-31VA	26,3 - 31,0	10,0
2OK28-31VA	28,0 - 31,0	9,0
2OK31-34VA	31,0 - 34,0	9,5
2OK34-37VA	34,0 - 37,0	9,5
2OK37-40VA	37,0 - 40,0	10,0
2OK40-43VA	40,0 - 43,0	10,0
2OK43-46VA	43,0 - 46,0	10,0