

Характеристики

Область применения	Крепления шлангов в области низких и средних давлений.
Материал	Сталь
Защита поверхности	Блестящее цинкование и хроматирование



Артикул

Наименование	Диапазон зажима (мм)	Ширина ленты
2OK3-5VC	3,0 - 5,0	5,0
2OK3.1-4.1VC	3,1 - 4,1	3,5
2OK3.5-4.5VC	3,5 - 4,5	3,5
2OK5-7VC	5,0 - 7,0	6,0
2OK7-9VC	7,0 - 9,0	7,0
2OK8-11VC	8,0 - 11,0	7,0
2OK9-11VC	9,0 - 11,0	7,0
2OK11-13VC	11,0 - 13,0	7,0
2OK13-15VC	13,0 - 15,0	7,5
2OK15-17VC	15,0 - 17,0	8,0
2OK15-18VC	15,0 - 18,0	8,0
2OK16-19VC	16,0 - 19,0	8,0
2OK17-20VC	17,0 - 20,0	8,5
2OK19-22VC	19,0 - 22,0	9,0
2OK20-23VC	20,0 - 23,0	9,0
2OK22-25VC	22,0 - 25,0	10,0
2OK23-25VC	23,0 - 25,0	10,0
2OK23-27VC	23,0 - 27,0	10,0
2OK25-28VC	25,0 - 28,0	10,0
2OK27-31VC	27,0 - 31,0	10,0
2OK28-31VC	28,0 - 31,0	10,0
2OK31-34VC	31,0 - 34,0	10,0
2OK34-37VC	34,0 - 37,0	10,0
2OK37-40VC	37,0 - 40,0	10,0
2OK40-43VC	40,0 - 43,0	10,0
2OK43-46VC	43,0 - 46,0	10,0