

Характеристики

Свойства

Soft, flexible folds
Soft, tapered sealing lips
Support surfaces on the bottom
high suction power
optimum damping effect
very good adaptation to curved or uneven material

Область применения

Handling of highly uneven parts (e.g.tubes)
Handling of highly sensitive parts

Дополнительная**информация**

Achtung: Anschlussnippel sind nicht im Preis enthalten, bitte separat bestellen.



Указания

Прочие данные только по запросу. Mini-sensor with housing and connection cable, analogue or digital output signal. Minimum size and low weight combined with high measuring accuracy.

Описание

Robust and hard-wearing suction pad with a single sealing lip. Used wherever objects (parts, packing materials, etc.) need to be lifted, transported, turned over or handled in some other manner. It is also ideal when it is necessary to compensate varying workpiece heights or uneven surfaces or to handle easily damaged parts. It acts as the connecting element between the vacuum generator and the workpiece.

Дополнительная информация

Attention: The price does not include connection nipples. Please order separately.

Артикул

Наименование	Соединительный ниппель с внешней резьбой	Соединительный ниппель с внутренней резьбой	Габаритная высота с ниппелем (наружная резьба)	Габаритная высота с ниппелем (внутренняя резьба)	Ø
K-07450045	K-07450001	K-07450005	18,5	23,5	5,0
K-07450047	K-07450002 / K-07450004	K-07450007	19 / 20	26	7,0
K-07450049	K-07450002 / K-07450004	K-07450007	20 / 21	27	9,0
K-07450051	K-07450002 / K-07450004	K-07450007	26 / 27	33	12,0
K-07450053	K-07450002 / K-07450004	K-07450007	27 / 28	34	14,0
K-07450055	K-07450002 / K-07450004	K-07450007	27 / 28	34	18,0
K-07450057	K-07450002 / K-07450004	K-07450007	27 / 28	34	20,0
K-07450059	K-07450004	K-07450007	40	46	25,0
K-07450061	K-07450003	K-07450006	41,5	52,5	32,0
K-07450063	K-07450003	K-07450006	50	61	42,0
K-07450065	K-07450003	K-07450006	53	64	52,0