

Характеристики

Область температур	-10 °C to +50 °C
Рабочее давление	Max. 15 bar
Корпус	Glass fibre-reinforced plastic
Резьба	Brass
Дополнительная информация	4 Nm Drehmoment Befestigung 12 Nm Drehmoment MS- Gewinde



Указания

Прочие данные только по запросу.

Описание

1, 2 or 3-way porting boxes made of high-strength glass fibre-reinforced plastic for a wide range of applications. Available with up to 3 couplings and 2 inlet thread sizes. Optional through-hole thread at the bottom to facilitate the passage of the medium. All porting boxes have a robust, brass threaded insert for high tightening torques, TÜV certified. Suitable for almost any pneumatic application.

Дополнительная информация

4 Nm torque mounting hole
12 Nm torque brass thread

Артикул

Наименование	Проходная резьба	Соединительная резьба	Резьба на входе
K-07404804	G 1/2	1 x G 1/2	G 1/2"
K-07404805	G 1/2	2 x G 1/2	G 1/2"
K-07404806	G 1/2	3 x G 1/2	G 1/2"
K-07404807	G 3/4	1 x G 1/2	G 3/4"
K-07404808	G 3/4	2 x G 1/2	G 3/4"
K-07404809	G 3/4	3 x G 1/2	G 3/4"