

### Характеристики

<b>Применение</b>	Handling of workpieces with differing heights (eg. Curved metal sheets) Handling of very sensitive workpieces, very soft landing is assured
<b>Температура min.</b>	0 °C
<b>Температура макс.</b>	80 °C
<b>Подключение</b>	M 3 female
<b>вытяжки</b>	
<b>Исполнение</b>	Spring plunger with high-strength steel rod, guide sleeve and lower damping spring Plunger rod with integrated vacuum guide
<b>Ход пружины</b>	5 mm



### Указания

Прочие данные только по запросу.

### Описание

Suitable for all round or oval suction pads in our standard range.

### Артикул

Наименование	Вертикальная нагрузка	Ход пружины	Длина
<a href="#">K-07450073</a>	550	5,0	33,5
<a href="#">K-07450076</a>	1,500	5,0	41,2
<a href="#">K-07450074</a>	1,500	10,0	47,2
<a href="#">K-07450075</a>	1,500	20,0	59,2
<a href="#">K-07450070</a>	3,700	15,0	80,0
<a href="#">K-07450067</a>	3,700	25,0	95,0
<a href="#">K-07450071</a>	3,700	25,0	93,0
<a href="#">K-07450068</a>	2,400	50,0	124,5
<a href="#">K-07450072</a>	2,400	50,0	124,0
<a href="#">K-07450069</a>	2,400	75,0	154,0