

Характеристики

Свойства

Support surfaces on the bottom

minimal priming
high lateral forces realized
good stability in the sucked state
fastest cycle times

Область применения

Handling of parts with plain to an slightly rough surface like sheets, cartons, glass, plastics

Дополнительная информация

Achtung: Anschlussnippel sind nicht im Preis enthalten, bitte separat bestellen.



Указания

Прочие данные только по запросу. Mini-sensor with housing and connection cable, analogue or digital output signal. Minimum size and low weight combined with high measuring accuracy.

Описание

Robust and hard-wearing suction pad with a single sealing lip. Used wherever objects (parts, packing materials, etc.) need to be lifted, transported, turned over or handled in some other manner. It is also ideal when it is necessary to handle smooth or slightly rough surfaces. Due to its flat shape, it can grip the workpiece in a very short time and withstand the forces that result from fast movement of the object during handling. It acts as the connecting element between the vacuum generator and the workpiece.

Дополнительная информация

Attention: The price does not include connection nipples. Please order separately.

Артикул

Наименование	Соединительный ниппель с внешней резьбой	Соединительный ниппель с внутренней резьбой	Габаритная высота с ниппелем (наружная резьба)	Габаритная высота с ниппелем (внутренняя резьба)	Ø
K-07450088	K-07450014	-	6	-	3,5
K-07450090	K-07450015	K-07450022	11,5	16,5	5,0
K-07450092	K-07450015	K-07450022	12	17	8,0
K-07450094	K-07450015 / K-07450017	K-07450022 / K-07450024	12,5	17,5 / 23,5	10,0
K-07450096	K-07450018	K-07450025	13	24	15,0
K-07450098	K-07450019	K-07450026	15	26	20,0
K-07450100	K-07450020	K-07450027	19	30	25,0
K-07450102	K-07450020	K-07450027	17	28	30,0
K-07450104	K-07450020	K-07450027	19	30	35,0
K-07450106	K-07450020	K-07450027	19	30	40,0
K-07450108	K-07450021	K-07450028	20	31	50,0
K-07450110	K-07450016	K-07450016	23	39	60,0
K-07450112	K-07450016	K-07450016	25	41	80,0