

Характеристики

Рабочие среды	Filtered (50 µm), unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.
Рабочее давление	1 to 8 bar
Область температур	-15 °C to +80 °C
Корпус	Jacket made from anodised aluminium alloy
внутренняя/внешняя лента	Stainless steel
Уплотнение	NBR for speeds up to 1 m/s
Салазки (направляющие поршня)	Anodised aluminium alloy
Дополнительная информация	Wichtiger Hinweis: Stecker im Lieferumfang nicht enthalten. Bitte separat mitbestellen.



Указания

Прочие данные только по запросу.

Описание

These double-acting cylinders can also be supplied with strokes greater than 5 m, providing the stroke length is approximately equal to the overall length. They are equipped with magnets as standard for indicating the position as well as pneumatic, adjustable end position cushioning. Limit switches and hydraulic shock absorbers can be mounted as add-on modules.

Указание по заказу

All strokes can also be supplied in 1 mm steps on request. Ø 16 to 5000 mm, Ø 25, 32, 40 to 5700 mm and Ø 63 to 5500 mm. Versions with an integrated linear guide can be supplied on request (up to 50 x lateral load).

Дополнительная информация

Important: The scope of supply does not include a connector. Please order separately.

Артикул

Наименование	Усилие 6 бар	Ход	макс. боковая нагрузка
K-07150734	110	100	0,3
K-07150735	110	200	0,3
K-07150736	110	300	0,3
K-07150737	110	400	0,3
K-07150738	110	500	0,3
K-07150739	110	600	0,3
K-07150740	110	700	0,3
K-07150741	110	800	0,3
K-07150742	110	900	0,3
K-07150743	110	1000	0,3
K-07150744	110	1200	0,3
K-07150745	110	1400	0,3
K-07150746	110	2000	0,3
K-07150747	250	100	1,0
K-07150748	250	200	1,0
K-07150749	250	300	1,0
K-07150750	250	400	1,0
K-07150751	250	500	1,0
K-07150752	250	600	1,0

Наименование	Усилие 6 бар	Ход	макс. боковая нагрузка
K-07150753	250	700	1,0
K-07150754	250	800	1,0
K-07150755	250	900	1,0
K-07150756	250	1000	1,0
K-07150757	250	1200	1,0
K-07150758	250	1400	1,0
K-07150759	250	2000	1,0
K-07150760	420	100	2,0
K-07150761	420	200	2,0
K-07150762	420	300	2,0
K-07150763	420	400	2,0
K-07150764	420	500	2,0
K-07150765	420	600	2,0
K-07150766	420	700	2,0
K-07150767	420	800	2,0
K-07150768	420	900	2,0
K-07150769	420	1000	2,0
K-07150770	420	1200	2,0
K-07150771	420	1400	2,0
K-07150772	420	2000	2,0
K-07150773	640	100	4,0
K-07150774	640	200	4,0
K-07150775	640	300	4,0
K-07150776	640	400	4,0
K-07150777	640	500	4,0
K-07150778	640	600	4,0
K-07150779	640	700	4,0
K-07150780	640	800	4,0
K-07150781	640	900	4,0
K-07150782	640	1000	4,0
K-07150783	640	1200	4,0
K-07150784	640	1400	4,0
K-07150785	640	2000	4,0
K-07150786	1550	100	8,0
K-07150787	1550	200	8,0
K-07150788	1550	300	8,0
K-07150789	1550	400	8,0
K-07150790	1550	500	8,0
K-07150791	1550	600	8,0
K-07150792	1550	700	8,0
K-07150793	1550	800	8,0
K-07150794	1550	900	8,0
K-07150795	1550	1000	8,0
K-07150796	1550	1200	8,0
K-07150797	1550	1400	8,0
K-07150798	1550	2000	8,0