

Характеристики

Соединение	4-pin connection for headphones and charger, 3.5 mm stereo jack for connecting sensor and cable
Дополнительная информация	Arbeitsfrequenz 40 kHz \pm 2 kHz Einsatztemperatur 0 °C bis +40 °C Lagertemperatur -10 °C bis +50 °C Laser Wellenlänge: 655...660 nm, Ausgangsleistung: 0,4...0,5 mW Betriebsdauer ca. 6 Stunden ohne Laser / 4 Stunden mit Laser Energieversorgung interner NiMH Akku Ca. 1,5 Stunden Ladezeit



Указания

Прочие данные только по запросу.

Описание

Function: The annual energy cost of leaks in pneumatic and gas systems are high and avoidable. When these gases flow unused out of leaks, they create noises inaudible to the human ear. With the LS 100, even the smallest leaks can be heard from several metres distance. It transforms inaudible signals to a frequency that can be detected visually on the display and acoustically with the supplied sound-proof headphones. Use: leakage inspections of pneumatic, gas, steam and vacuum systems.

The advantages of the LS 100: Simple and quick measurement, even from distances of several metres. Measurements can be taken on running systems, without affecting their operation. The device is quickly amortised by the high cost savings.

Дополнительная информация

Working frequency 40 kHz \pm 2 kHz
Fit temperature 0 °C to +40 °C
Storage temperature -10 °C to +50 °C
Laser as a visual tool
Wave length: 655 to 660 nm, Output power: 0.4 to 0.5 mW
Operating time approx. 6 hours without laser / 4 hours with laser
Power supply internal NiMH rechargeable battery
Approx. 1.5 hours charging time

Артикул

Наименование

[K-07251953](#)