

Характеристики

Рабочие среды	Filtered, unlubricated compressed air
Диапазон давлений	0 - 7 bar (NC) with silver plate at manual override 0 - 5 bar (NO) with black plate at manual override
Соединение	In manifold base
Область температур	-5 °C to +45 °C
Мощность катушки	2.5 W
Материал	Пластмасса
Уплотнение	NBR, stainless steel
Дополнительная информация	Wichtiger Hinweis: Stecker im Lieferumfang nicht enthalten. Bitte separat mitbestellen. Öffnungszeit/Schließzeit 10 - 12 ms (druckabhängig)



Указания

Прочие данные только по запросу.

Описание

Directly controlled 3/2-way solenoid valves specially designed for pneumatic applications. These valves are provided with a flange for assembly on an individual base or multiple manifold base. They feature a monostable manual operator. The scope of supply includes two fixing bolts and a flange gasket. The coils can be turned 180°.

Дополнительная информация

Important: The scope of supply does not include a connector. Please order separately. Opening time/closing time 10 - 12 ms (depending on pressure)

Артикул

Наименование	Мощность катушки	Функция	В	Н
K-07151418	2,5	NC	15,0	42,0
K-07151419	2,5	NC	15,0	42,0
K-07151420	2,5	NC	15,0	42,0
K-07151421	2,5	NC	15,0	42,0
K-07151422	2,5	NO	15,0	42,0
K-07151423	2,5	NO	15,0	42,0
K-07151424	2,5	NO	15,0	42,0
K-07151425	2,5	NO	15,0	42,0