

### Характеристики

<b>Применение</b>	For all pressure gauges with a flat gasket acc. to DIN 16258
<b>Диапазон давлений</b>	Max. 16 bar, depending on the variant. Pressure gauge valves should be used for higher pressures
<b>Температура</b>	max. 50 °C
<b>Ручка</b>	Plastic
<b>Корпус</b>	Brass with a bare metal surface or stainless steel 1.4571
<b>Дополнительная информация</b>	Weitere Messbereiche auf Anfrage Ausführung für Fronttafeleinbau auf Anfrage Ausführung mit Schleppzeiger auf Anfrage
<b>Контрольный фланец</b>	-



### Указания

Прочие данные только по запросу. K-07201090, K-07201091 in acc. with DIN 16261-A, K-07201096, K-07201097 in acc. with DIN 16261-B K-07201128, K-07201129 in acc. with DIN 16262-A, K-07201127 in acc. with DIN 16262-B

### Описание

It is useful to install a stopcock as a shut-off element between the pressure gauge and the pipe. When the lever is set to the »blow out« position, the medium is discharged into the atmosphere. Stopcocks with a test port allow pressure gauges to be simultaneously connected to the pipe.

### Дополнительная информация

Further measuring ranges on request. Version for panel mounting available on request. Version with max. pointer available on request

### Артикул

Наименование	PN (бар)	SW	Резьба
<a href="#">K-07201094</a>	6	17	G 1/4
<a href="#">K-07201095</a>	16	22	G 3/8
<a href="#">K-07201097</a>	25	27	G 1/2
<a href="#">K-07201096</a>	25	27	G 1/2
<a href="#">K-07201098</a>	25	27	G 1/2