

Характеристики

Применение	For all pressure gauges with a flat gasket acc. to DIN 16258
Диапазон давлений	Max. 16 bar, depending on the variant. Pressure gauge valves should be used for higher pressures
Температура	Max. 50 °C
Ручка	Plastic
Корпус	Brass with a bare metal surface or stainless steel 1.4571
Дополнительная информация	Weitere Messbereiche auf Anfrage Ausführung für Fronttafeleinbau auf Anfrage Ausführung mit Schleppzeiger auf Anfrage
Контрольный фланец	-



Указания

Прочие данные только по запросу. K-07201090, K-07201091 in acc. with DIN 16261-A, K-07201096, K-07201097 in acc. with DIN 16261-B K-07201128, K-07201129 in acc. with DIN 16262-A, K-07201127 in acc. with DIN 16262-B

Описание

It is useful to install a stopcock as a shut-off element between the pressure gauge and the pipe. When the lever is set to the »blow out« position, the medium is discharged into the atmosphere. Stopcocks with a test port allow pressure gauges to be simultaneously connected to the pipe.

Дополнительная информация

Further measuring ranges on request Version for panel mounting available on request. Version with max. pointer available on request

Артикул

Наименование	PN (бар)	SW	Резьба
K-07201127	6	17	G 1/4
K-07201129	25	27	G 1/2
K-07201128	25	27	G 1/2
K-07201131	25	27	G 1/2
K-07201130	25	27	G 1/2
K-07201132	25	27	G 1/2