

Характеристики

Область температур	-20 °C to +300 °C (at 20 bar)
Поверхность	Hot dip galvanised
Соединительная резьба	nach ISO 7-1
Материал	Black malleable iron B350-10, design symbol A
Допуск	DIN DVGW
Дополнительная информация	Weitere Typen und Größen auf Anfrage.



Указания

Прочие данные только по запросу.

Описание

Acc. to DIN EN 10242 (formerly DIN 2950). The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water. They are also protected against rust. The fittings are used in pipe construction, plumbing and gas installations as well as a wide range of industrial applications.

Указание по заказу

Attention: the thread sizes of Article K-07403704 have changed.

Дополнительная информация

Further types and dimensions on request.

Артикул

Наименование	Резьба 1	Резьба 2
K-07403714	Rp 3/8	Rp 1/4
K-07403704	Rp 1/2	Rp 1/4
K-07403705	Rp 1/2	Rp 3/8
K-07403712	Rp 3/4	Rp 1/4
K-07403713	Rp 3/4	Rp 3/8
K-07403711	Rp 3/4	Rp 1/2
K-07403696	Rp 1	Rp 3/8
K-07403694	Rp 1	Rp 1/2
K-07403695	Rp 1	Rp 3/4
K-07403703	Rp 1 1/4	Rp 3/8
K-07403701	Rp 1 1/4	Rp 1/2
K-07403702	Rp 1 1/4	Rp 3/4
K-07403700	Rp 1 1/4	Rp 1
K-07403698	Rp 1 1/2	Rp 1/2
K-07403699	Rp 1 1/2	Rp 3/4
K-07403697	Rp 1 1/2	Rp 1
K-07403735	Rp 1 1/2	Rp 1 1/4
K-07403709	Rp 2	Rp 1/2
K-07403710	Rp 2	Rp 3/4
K-07403706	Rp 2	Rp 1
K-07403708	Rp 2	Rp 1 1/4
K-07403707	Rp 2	Rp 1 1/2
K-07405168	Rp 2 1/2	Rp 2
K-07405169	Rp 3	Rp 1 1/2
K-07405170	Rp 3	Rp 2
K-07405171	Rp 3	Rp 2 1/2