

Spiral hose, with swivel adapter fitted at both ends and kink protector

Обновлено: 04.28.24

Характеристики

Применение	Air, gases, oils, greases, fuels, organic and inorganic substances
Рабочая температура	-40 °C to +100 °C
Вид подключения	connection nipples and coupling NW 7,2



Указания

Прочие данные только по запросу.

Описание

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

Артикул

Наименование	Внутренний Ø шланга	Внешний Ø шланга	max. Betriebsdruck bei 23°C	Внешний Ø спирали	Витки	Резьба	макс. рабочая длина
K-07100734	3,1	4,7	22	38	36	R 1/8	2,5
K-07100735	3,1	4,7	22	38	72	R 1/8	5,0
K-07100736	3,1	4,7	22	38	108	R 1/8	7,5
K-07100737	4,8	6,3	16	75	15	R 1/4	2,5
K-07100738	4,8	6,3	16	75	30	R 1/4	5,0
K-07100739	4,8	6,3	16	75	45	R 1/4	7,5
K-07100740	6,3	7,9	13	75	15	R 1/4	2,5
K-07100741	6,3	7,9	13	75	30	R 1/4	5,0
K-07100742	6,3	7,9	13	75	45	R 1/4	7,5
K-07100728	7,9	9,5	12	115	10	R 1/4	2,5
K-07100729	7,9	9,5	12	115	20	R 1/4	5,0
K-07100730	7,9	9,5	12	115	30	R 1/4	7,5
K-07100731	9,5	11,8	11	140	8	R 3/8	2,5
K-07100732	9,5	11,8	11	140	15	R 3/8	5,0
K-07100733	9,5	11,8	11	140	23	R 3/8	7,5