

### Характеристики

Рабочая температура -40 °C to +74 °C



### Указания

Прочие данные только по запросу.

### Описание

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

### Артикул

Наименование	Резьба	Внутренний Ø шланга	Внешний Ø шланга	max. Betriebsdruck bei 23°C	Ø внешнего витка	макс. рабочая длина
<a href="#">K-07100719</a>	G 1/4	5,0	8,0	10	40	3,0
<a href="#">K-07100720</a>	G 1/4	5,0	8,0	10	40	6,0
<a href="#">K-07100721</a>	G 1/4	5,0	8,0	10	40	7,5
<a href="#">K-07100722</a>	G 1/4	6,3	9,5	10	60	3,0
<a href="#">K-07100723</a>	G 1/4	6,3	9,5	10	60	6,0
<a href="#">K-07100724</a>	G 1/4	6,3	9,5	10	60	7,5
<a href="#">K-07101277</a>	G 1/4	6,3	9,5	10	60	10,0
<a href="#">K-07100725</a>	G 3/8	8,0	12,0	9	80	3,0
<a href="#">K-07100726</a>	G 3/8	8,0	12,0	9	80	6,0
<a href="#">K-07100727</a>	G 3/8	8,0	12,0	9	80	7,5
<a href="#">K-07101286</a>	G 3/8	8,0	12,0	9	80	10,0