

### Характеристики

<b>Рабочая температура</b>	-60 °C to +100 °C (PA 12)
<b>Длина трубы</b>	3 m
<b>Свойства</b>	Resistant to corrosion, vibration, impact, ageing, high pressures and heat
<b>Единица упаковки</b>	20 lengths (O.D. 28 mm in packs of 10 lengths), only sold in complete packaging units!
<b>Материал</b>	Polyamid PA 12, hard (according to DIN 73378)



### Указания

Прочие данные только по запросу. Operating pressure with 2.5 x overpressure safety!

### Описание

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

### Артикул

Наименование	макс. рабочее давление при 20°C	Наружный Ø трубы	Внутренний Ø трубы	Цвет
<a href="#">K-07100456</a>	38	12	9	синий
<a href="#">K-07100458</a>	38	12	9	черный
<a href="#">K-07100460</a>	25	15	12	синий
<a href="#">K-07100462</a>	25	15	12	черный
<a href="#">K-07100464</a>	28	18	14	синий
<a href="#">K-07100466</a>	28	18	14	черный
<a href="#">K-07100468</a>	22	22	18	синий
<a href="#">K-07100470</a>	22	22	18	черный
<a href="#">K-07100472</a>	20	28	23	синий
<a href="#">K-07100474</a>	20	28	23	черный