

Характеристики

Рабочая температура	-60 °C to +100 °C (PA 12)
Длина трубы	3 m
Свойства	Resistant to corrosion, vibration, impact, ageing, high pressures and heat
Единица упаковки	10 lengths (O.D. 28 mm in packs of 5 lengths), only sold in complete packaging units!
Материал	Polyamid PA 12, hard (according to DIN 73378)



Указания

Прочие данные только по запросу. Operating pressure with 2.5 x overpressure safety!

Описание

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

Артикул

Наименование	макс. рабочее давление при 20°C	Наружный Ø трубы	Внутренний Ø трубы	Цвет
K-07100457	38	12	9	синий
K-07100459	38	12	9	черный
K-07100461	25	15	12	синий
K-07100463	25	15	12	черный
K-07100465	28	18	14	синий
K-07100467	28	18	14	черный
K-07100469	22	22	18	синий
K-07100471	22	22	18	черный
K-07100473	20	28	23	синий
K-07100475	20	28	23	черный